



EndExam

QUESTION & ANSWER

Accurate study guides, High passing rate!



We offer free update service for one year!

<http://www.endexam.com>

Exam : **642-737**

Title : **Implementing Advanced
Cisco Unified Wireless**

Version : **DEMO**

1.Which two considerations must a network engineer have when planning for voice over wireless roaming?
(Choose two.)

- A. Roaming with only 802.1x authentication requires full reauthentication.
- B. Full reauthentication introduces gaps in a voice conversation.
- C. Roaming occurs when e phone has seen at least four APs.
- D. Roaming occurs when the phone has reached -80 dBs or below.

Answer: A,B

2.Which three of the items listed are required configuration parameters for the WLC to enable NAC out-of-band single sign-on when implementing NAC appliances? (Choose three.)

- A. EAP authentication
- B. web authentication
- C. SNMP
- D. RADIUS accounting
- E. WLAN > SNMP NAC enabled
- F. WLAN > RADIUS NAC enabled

Answer: C,D,E

3.An engineer is responding to a man-in-the-middle attack and needs to enable security features to prevent such attacks in the future. What security feature would prevent a manin-the-middle attack?

- A. Management Frame Protection
- B. ACL
- C. Enable client and infrastructure MFP
- D. AAA Override

Answer: C

4.Refer to the exhibit.

The screenshot shows the 'WLANs > Edit' configuration page in Cisco WLC v7.0, with the 'Security' tab selected. The 'Client Exclusion' feature is enabled with a 'Timeout Value (secs)' of 0. Other security features like 'Management Frame Protection (MFP)' and 'DTIM Period' are also visible.

| Feature | Configuration |
|--|--|
| Allow AAA Override | <input type="checkbox"/> Enabled |
| Coverage Hole Detection | <input checked="" type="checkbox"/> Enabled |
| Enable Session Timeout | <input checked="" type="checkbox"/> 1800 Session Timeout (secs) |
| Aironet IE | <input checked="" type="checkbox"/> Enabled |
| Diagnostic Channel | <input type="checkbox"/> Enabled |
| IPv6 Enable | <input type="checkbox"/> |
| Override Interface ACL | None |
| P2P Blocking Action | Disabled |
| Client Exclusion | <input checked="" type="checkbox"/> Enabled Timeout Value (secs): 0 |
| HREAP | |
| H-REAP Local Switching | <input type="checkbox"/> Enabled |
| Learn Client IP Address | <input checked="" type="checkbox"/> Enabled |
| DHCP | |
| DHCP Server | <input type="checkbox"/> Override |
| DHCP Addr. Assignment | <input type="checkbox"/> Required |
| Management Frame Protection (MFP) | |
| Infrastructure MFP Protection | <input checked="" type="checkbox"/> (Global MFP Disabled) |
| MFP Client Protection | Optional |
| DTIM Period (in beacon intervals) | |
| 802.11a/n (1 - 255) | 1 |
| 802.11b/g/n (1 - 255) | 1 |
| NAC | |
| State | <input type="checkbox"/> Enabled |

What is the effect of setting Client Exclusion to Enabled and set to a Timeout Value of 0 seconds in a Cisco WLC v7.0?

- A. Excluded clients must be manually removed from the excluded list.
- B. Client exclusion will not occur.
- C. Client exclusion timeout will be determined by the IDS module.
- D. Clients will only be disconnected and not excluded.

Answer: A

5.What NAC appliance component is configured to create user roles, meet remediation requirements, and handle checking for device compliance?

- A. NGS
- B. NAA
- C. NAS
- D. NAM

Answer: D